LOC/DME I-LUK	APP CRS	Rwy Idg	6101
110.9	205°	TDZE	475
Chan 46		Apt Elev	483

ILS or LOC RWY 21L

CINCINNATI MUNI AIRPORT-LUNKEN FIELD (LUK)

Visibility reduction by helicopters NA. When local altimeter setting not received, use Cincinnati/Northern Kentucky Intl altimeter setting and increase all DA 86 feet and all MDA 100 feet. For KEELY OM Minimums: increase S-LOC-21L Cats. C and D, Circling Cats. A, B and D visibility ¼ mile, Circling Cat. C visibility ½ mile. Inoperative table does not apply to S-LOC-21L Cat. A. VDP NA when using Cincinnati/Northern Kentucky Intl altimeter setting. For inoperative MALSR, increase S-LOC-21L Cat. B visibility ¼ mile. For KEELY OM Minimums: Increase S-LOC-21L Cats. A and B visibility ¼ mile. When using Cincinnati/Northern Kentucky Intl altimeter setting: Increase S-ILS-21L all Cats. visibility ½ mile.

MALSR

MISSED APPROACH: Climb to 2000 then climbing left turn to 2600 via heading 140° and CVG VORTAC R-109 to CALIF INT/CVG 19 DME and hold.

ATIS	CINCINNATI APP CON	LUNKEN TOWER ★	GND CON	CLNC DEL	UNICOM
120.25	121.0 257.725	118.7 (CTAF) L 257.8	121.9	121.9	122.95

ADF REQUIRED

025° 250° 070° 205° 3000 244° (8.6) MOAKS

MSA MDE 25 NM 3000

IAF MADEIRA 379 MDE I-LUK 8.5

KEELY OM 676± I-LUK 4.6

10 NM

LOCALIZER 110.9 I-LUK Chan 46

FALMOUTH 117.0 FLM Chan 117

ALTERNATE MISSED APCH FIX FALMOUTH FLM 117.0 Chan 117 R-324 144° 324°

MISSED APCH FIX 117.3 CVG Chan 120 109° 289° R-109 CALIF CVG 19 R-004 117.0 FLM Chan 117

ELEV 483

205° 7.3 NM from FAA

TWR 553

TDZE 475

5128 X 100 3802 X 100 6101 X 150

REIL Rwy 3R

HIRL Rwy 3R-21L L

MIRL Rwy 3L-21R and 7-25

FAF to MAP 7.3 NM					
Knots	60	90	120	150	180
Min:Sec	7:18	4:52	3:39	2:55	2:26

2000	2600	CVG R-109 117.3	CALIF
	140°		

* LOC only.

NDB I-LUK 8.5

Remain within 10 NM

KEELY OM I-LUK 4.6 I-LUK 2.9 I-LUK 1.2 2902 1607 1600* 025° 205° 3000 3000

GS 3.00° TCH 39

1.7 1.7 3.9 NM

CATEGORY	A	B	C	D
S-ILS 21L	750/40 275 (300-¾)			
S-LOC 21L	1600/60 1125 (1200-1¼)		1600-2½ 1125 (1200-2½)	
CIRCLING	1600-1¼ 1117 (1200-1¼)	1600-1½ 1117 (1200-1½)	1600-3 1117 (1200-3)	
KEELY OM MINIMUMS				
S-LOC 21L	1040/40 565 (600-¾)		1040/50 565 (600-1)	1040/60 565 (600-1¼)
CIRCLING	1300-1 817 (900-1)	1360-1¼ 877 (900-1¼)	1360-2½ 877 (900-2½)	1360-2¾ 877 (900-2¾)

EC-2, 22 OCT 2009 to 19 NOV 2009
EC-2, 22 OCT 2009 to 19 NOV 2009