WAAS CH 56200 W28A	APP CRS 277°	Rwy ldg 9010 TDZE 197 Apt Elev 221

RNAV (GPS) RWY 28
MONTGOMERY RGNL (DANNELLY FIELD) (MGM)

GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA. Baro-VNAV NA below -15° C (5° F). For inoperative MALSR, increase LPV Cat. E visibility to 1 and LNAV/VNAV Cat. E and LNAV Cat. D/E visibility to 1¼. Circling NA at night to Rwy 21. Circling NA for Cat. E North of Rwy 10-28.

MALSR

MISSED APPROACH: Climb to 3100 direct HEGAP and hold.

ATIS	MONTGOMERY APP CON ★	DANNELLY TOWER ★	GND CON	CLNC DEL
120.675	121.2 380.225	119.7(CTAF) L 360.85	121.7 348.6	118.3 270.3





CATEGORY	A	B	C	D	E
LPV DA	500-½ 303 (300-½)				
LNAV/VNAV DA	560-¾ 363 (400-¾)				
LNAV MDA	580-½ 383 (400-½)			580-1 383 (400-1)	
CIRCLING	700-1¼ 479 (500-1¼)		700-1½ 479 (500-1½)	800-2 579 (600-2)	

SE-4, 22 OCT 2009 to 19 NOV 2009