

RNAV (GPS) RWY 32

GULFPORT-BILOXI INTL (GPT)

WAAS CH 56207 W32A	APP CRS 313°	Rwy Idg 9002 TDZE 28 Apt Elev 28
--	------------------------	---

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Pascagoula altimeter setting and increase all DA 67 feet and all MDA 80 feet, increase LNAV/VNAV visibility all Cats to 1½ mile, LNAV visibility Cat C to RVR 5000, Cat D to RVR 6000, increase circling visibility Cat C to 2 and Cat D to 2½ mile. Inoperative table does not apply to LPV all Cats. For inoperative MALSR, increase LNAV Cat A and B visibility to RVR 5000. For inoperative MALSR when using Pascagoula altimeter setting, increase LNAV Cat A and B visibility to RVR 5000. VDP and Baro-VNAV NA when using Pascagoula altimeter setting.

MALSR

MISSED APPROACH:
Climb to 2000 direct BROWA and hold.

ATIS 119.45	GULFPORT APP CON * 124.6 254.25	GULFPORT TOWER * 123.7 (CTAF) 339.8	GND CON 120.4 348.6	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------

