ILS or LOC RWY 32

SHREVEPORT RGNL (SHV)

LOC I-FOG	APP CRS	Rwy Idg	7976
110.3	319°	TDZE	222
		Apt Elev	258

ASR: Inoperative table does not apply to S-ILS 32 all Cats. For inoperative MALSR, increase S-LOC 32 Cats. A, B and C visibility to RVR 5000. Visibility reduction by helicopters NA.

MALSR

MISSED APPROACH: Climb to 800 then climbing right turn to 3100 via EIC R-184 to EIC VORTAC and hold.

ATIS	SHREVEPORT APP CON	SHREVEPORT TOWER	GND CON	CLNC DEL
128.45	119.9 335.55	121.4 236.775	121.9 236.775	124.65

MISSED APCH FIX
BELCHER
117.4 EIC
Chan 121

111° 291° R-111

BELCHER
117.4 EIC
Chan 121

ALTERNATE MISSED APCH FIX
ELM GROVE
111.2 EMG
Chan 49

143° 323° R-143

ELM GROVE
111.2 EMG
Chan 49

1046 EIC R-184

167° (24)

2100

10 NM

739 669 451 445 428 426 440 359 408 540 368± 408

LOCALIZER 110.3
I-FOG

319°

R-252

(IAF)
FORBE
OM/INT

1 min
319°
139°

139°

1049

MSA EMG 25 NM
3100

ELEV 258 D
283
270
TWR
339
14
32
07° DOWN
299
6202 X 150
5
23
8351 X 200
318
TDZE
222
306
32

REIL Rwy 5 and 23
HIRL Rwy 14-32
MIRL Rwy 5-23
TDZ/CL Rwy 14

319° 4.8 NM from FAF

FAF to MAP 4.8 NM					
Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

800	3100	EIC R-184	EIC 117.4

FORBE OM/INT
1817
139°
1900
319°
1900
319°
4.8 NM

One Minute Holding Pattern

GS 3.00°
TCH 52

CATEGORY	A	B	C	D
S-ILS 32	422/40 200 (200-¾)			
S-LOC 32	720/40 498 (400-¾)			720/50 498 (400-1)
CIRCLING	800-1 542 (600-1)		800-1½ 542 (600-1½)	820-2 562 (600-2)

SC-4, 22 OCT 2009 to 19 NOV 2009

SC-4, 22 OCT 2009 to 19 NOV 2009