WAAS	APP CRS	Rwy Idg	4600
CH 99401	223°	TDZE	2132
W22A		Apt Elev	2135

RNAV (GPS) RWY 22

OLEAN / CATTARAUGUS COUNTY-OLEAN (OLE)

DME/DME RNP-0.3 NA. When VGSI inop, straight-in/circling Rwy 22 procedure NA at night. If local altimeter setting not received, use Bradford, PA altimeter setting and increase all DAs/MDAs 80 feet. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 43°C (110°F). Baro-VNAV NA when using Bradford, PA altimeter setting. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 4000 direct VAKTY and hold.

AWOS-3	CLEVELAND CENTER	UNICOM
118.375	124.325 353.850	122.8 (CTAF) L

CATEGORY	A	B	C	D
LPV DA	2382-1 250 (300-1)			
LNAV/ VNAV DA	2569-1½ 437 (500-1½)			
LNAV MDA	2560-1 428 (500-1)		2560-1¼ 428 (500-1¼)	2560-1½ 428 (500-1½)
CIRCLING	2620-1½ 485 (500-1½)			2700-2 565 (600-2)

HIRL Rwy 4-22 L
REIL Rwys 4 and 22 L

NE-2, 22 OCT 2009 to 19 NOV 2009
NE-2, 22 OCT 2009 to 19 NOV 2009