

OBRNL TWO DEPARTURE

EC-2, 22 OCT 2009 to 19 NOV 2009

TAKE-OFF MINIMUMS:

- Rwy 6L, 400-2 or STANDARD with minimum climb of 400 feet per NM to 1800'.
- Rwy 6R, 400-2 or STANDARD with minimum climb of 360 feet per NM to 1800'.
- Rwy 24L, 300-1½ or STANDARD with minimum climb of 527 feet per NM to 1900'.
- Rwy 24R, 200-1 or STANDARD with minimum climb of 527 feet per NM to 1900'.

ATIS 125.25
CLEVELAND DEP CON
125.35 346.325

FORT WAYNE FWA	Chan 125
117.8	
N40°58.74'	
W85°11.28'	
L-27, H-5-10	

MUNCIE MIE	Chan 91
114.4	
N40°14.24'	
W85°23.64'	
L-27	

FINDLAY FDY	Chan 19
108.2	
N40°57.32'	
W83°45.36'	

OBRNL	Chan 83
N41°06.39'	
W82°44.09'	

CHARDON CXR	Chan 74
112.7	
N41°21.48'	
W82°09.72'	
L-30, H-10	

DRYER DJB	Chan 83
113.6	
N41°21.48'	
W82°09.72'	
L-30, H-10	



BRUNZ	Chan 83
N41°12.60'	
W82°30.02'	
3500	

MANSFIELD MFD	Chan 25
108.8	

ROSEWOOD ROD	Chan 122
117.5	
N40°17.27'	
W84°02.59'	
L-27, H-10	

RICHMOND RID	Chan 43
110.6	
N39°45.30'	
W84°50.33'	
L-27, H-10	

BRICKYARD VHP	Chan 110
116.3	
N39°48.88'	
W86°22.05'	
L-27, H-5-10	



NOTE: RADAR required
NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

OBRNL TWO DEPARTURE

EC-2, 22 OCT 2009 to 19 NOV 2009