

SABINE PASS ONE DEPARTURE (RNAV)

SC-5, 22 OCT 2009 to 19 NOV 2009

NOTE: Chart not to scale.

Note: RADAR Required.

Note: RNAV 1.

Note: DME/DME/IRU or GPS Required.

Note: For non-GPS equipped aircraft,

BPT and LCH must be operational.

TAKE-OFF MINIMUMS:

Rwy 17R, 35L Standard.

Rwy 17L, 35R, NA - Environmental.

Waterway 17, 35 NA - Air Traffic.

DAISETTA
DAS



HUMBLE
IAH



YOKEM

HOBBY
HUB



079°
(19)

097°
(16)

LINGG

SABINE PASS
SBI

10000

086°
(87)

WHITE LAKE
LLA



FL180

098°
(122)

LEEVILLE
LEV



ATIS 124.95
CLNC DEL 119.45
GND CON
121.8 239.0
HOOKS TOWER ★
127.4 354.1 (EAST)
118.4 (CTAF) 354.1 (WEST)
HOUSTON DEP CON
119.7 281.4

TAKE-OFF OBSTACLES:

Rwy 17R, Multiple trees beginning 708' from DER, 68' left of centerline, up to 71' AGL/
220' MSL. Multiple hangars beginning 433' from DER, 51.5' left of centerline, up to
37' AGL/182' MSL. DME antenna 653' from DER, 256' left of centerline, 13' AGL/
162' MSL. Multiple trees and pole beginning 85' from DER, 294' right of centerline,
up to 45' AGL/189' MSL.

Rwy 35L, Multiple trees and poles beginning 144' from DER, 32' left of centerline, up
to 79' AGL/238' MSL. Multiple hangars and buildings beginning 85' from DER, 9' left
of centerline, up to 53' AGL/202' MSL. Multiple trees, towers and pole beginning
100' from DER, 124' right of centerline, up to 93' AGL/247' MSL. Vehicle and road
315' from DER, on centerline 15' AGL/166' MSL. Building 894' from DER, 231' right
of centerline, 23' AGL/173' MSL.

DEPARTURE ROUTE DESCRIPTION

Expect vectors to LINGG, maintain 4000, then via depicted route to
SBI VOR/DME, thence. . . .

. . . via (transition). Expect clearance to filed altitude/flight level 10
minutes after departure.

LEEVILLE TRANSITION: (SBI1.LEV)

WHITE LAKE TRANSITION: (SBI1.LLA)

SABINE PASS ONE DEPARTURE (RNAV)

SC-5, 22 OCT 2009 to 19 NOV 2009