LOC/DME I-FGH	APP CRS	Rwy Idg 4775
109.35	041°	TDZE 58
Chan 30 (Y)		Apt Elev 72

ILS or LOC/DME RWY 4

EASTON/NEWNAM FIELD (ESN)

If local altimeter setting not received, use Baltimore-Washington Intl Thurgood Marshall altimeter setting and increase DA to 358 feet and all MDAs 100 feet. VDP NA when using Baltimore-Washington Intl Thurgood Marshall altimeter setting.

MISSED APPROACH: Climb to 2000 via heading 041° and ATR VOR/DME R-283 to ORETE INT/ATR 31.6 DME and hold.

ATIS	POTOMAC APP CON	EASTON TOWER★	GND CON	CLNC DEL	UNICOM
124.475	124.55 317.425	118.525 (CTAF) L	119.075	119.075 126.9 (Tower closed)	122.95

DME REQUIRED

LOCALIZER 109.35 I-FGH Chan 30 (Y)

ORETE ATR 31.6

111.4 ENO R-226 Chan 51

112.6 ATR R-283 Chan 73

103° 283°

163 227 238 291 389

WEGRO I-FGH 5.7

1600 041° (6.1)

(IF/IAF) RIKME I-FGH 11.8

221° 1 min 041° 221°

10 NM

564

R-4006

ALTERNATE MISSED APCH FIX

RIDGY ENO 21.5

046° 226°

4500 035° (23 A)

PATUXENT 117.6 PXT Chan 123

ELEV 72 D

15 0.5% UP 4003 X 100

12 5500 X 100

33 0.7% UP TDZE 58

041° 4.7 NM from FAF

139

HIRL Rwy 4-22 L

REIL Rwys 4, 22, 15 and 33 L

MIRL Rwys 15-33 L

One Minute Holding Pattern

RIKME I-FGH 11.8

WEGRO I-FGH 5.7

2000 221° 041° 041° 1600 I-FGH 2.5 I-FGH 1

GS 3.00° TCH 44

1600

6.1 NM 3.2 1.5

2000 hdg 041°

ATR 112.6 R-283

ORETE △

CATEGORY	A	B	C	D
S-ILS 4	265-¾ 207 (200-¾)			
S-LOC 4	540-1 482 (500-1)		540-1¼ 482 (500-1¼)	540-1½ 482 (500-1½)
CIRCLING	540-1 468 (500-1)		660-1½ 588 (600-1½)	660-2 588 (600-2)

NE-3, 22 OCT 2009 to 19 NOV 2009
NE-3, 22 OCT 2009 to 19 NOV 2009