

# SABINE PASS ONE DEPARTURE (RNAV)

SC-5, 22 OCT 2009 to 19 NOV 2009

HOUSTON DEP CON  
123.8 257.7  
CTAF  
122.8

Note: RADAR Required.  
Note: RNAV 1.  
Note: DME/DME/IRU or GPS Required.  
Note: For non-GPS equipped aircraft,  
BPT and LCH must be operational.

### TAKE-OFF MINIMUMS:

Rwy 27 Standard.  
Rwy 9, 300-1 or standard with a  
minimum climb of 399' per NM to 400.

DAISETTA  
DAS



HUMBLE  
IAH



YOKEM

HOBBY  
HUB



079°  
(119)

097°  
(116)

SABINE PASS  
SBI

10000  
086°  
(87)

WHITE LAKE  
LLA



FL180  
098°  
(122)



LEEVILLE  
LEV



### TAKE-OFF OBSTACLES:

Rwy 9, Tank, 4172' from DER, 1455' left of centerline, 147' AGL/282' MSL.  
Rwy 27, Railroad 462' from DER, 555' left of centerline, 23' AGL/165' MSL.  
Vehicle and road 650' from DER, 7' left of centerline, 17' AGL/159' MSL.

### DEPARTURE ROUTE DESCRIPTION

When entering controlled airspace, fly assigned heading for vectors to LINGG, maintain 4000, then via depicted route to SBI VOR/DME, thence . . .

. . . via (transition). Expect clearance to filed altitude/flight level 10 minutes after departure.

LEEVILLE TRANSITION: (SB11.LEV)

WHITE LAKE TRANSITION: (SB11.LLA)

NOTE: Chart not to scale.