

RADAR MINS

N1

09295

RADAR INSTRUMENT APPROACH MINIMUMS

AKRON, OH

Amdt. 23, July 5, 2007 (FAA)

ELEV 1228

AKRON-CANTON RGNL

RADAR - 125.5 371.875 (EAST) 118.6 323.0 (WEST) ▽ ▲

	RWY	GS/TCH/RPI	CAT	DA/	HAT/	HAA	CEIL-VIS	CAT	DA/	HAT/	HAA	CEIL-VIS
				MDA-VIS	HATH/				MDA-VIS	HATH/		
ASR	1		ABC	1580/24		371	(400-½)	D	1580/50		371	(400-1)
	5		ABC	1580-1		378	(400-1)	D	1580-1¼		378	(400-1¼)
	19		ABC	1580/24		362	(400-½)	D	1580/50		362	(400-1)
	23		ABC	1620/24		392	(400-½)	D	1620/50		392	(400-1)
CIRCLING			A	1660-1		432	(500-1)	B	1680-1		452	(500-1)
			C	1680-1½		452	(500-1½)	D	1780-2		552	(600-2)

Procedure NA when Akron-Canton approach control closed. For inoperative MALS R, increase S-19 CAT D visibility to RVR 6000, S-19 CAT D visibility to RVR to 6000, and S-23 CAT D visibility to RVR 6000.

DAYTON, OH

Amdt. 9, OCT 22, 2009 (FAA)

ELEV 1010

JAMES M. COX DAYTON INTL

RADAR - 118.425 126.5 134.45 294.5 352.05 ▽

	RWY	GS/TCH/RPI	CAT	DA/	HAT/	HAA	CEIL-VIS	CAT	DA/	HAT/	HAA	CEIL-VIS
				MDA-VIS	HATH/				MDA-VIS	HATH/		
ASR	6L		ABC	1380/24		382	(400-½)	D	1380/50		382	(400-1)
	36		AB	1420-1		411	(500-1)	CD	1420-1¼		411	(500-1¼)
CIRCLING			AB	1480-1		471	(500-1)	C	1480-1½		471	(500-1½)
			D	1560-2		551	(600-2)					

For inoperative ALSF-2 increase S-6L Category D visibility to RVR 6000.

EVANSVILLE, IN

Amdt. 6, MAY 7, 2009 (FAA)

ELEV 418

EVANSVILLE RGNL

RADAR-1 - 126.4 226.4 ▽

	RWY	GS/TCH/RPI	CAT	DA/	HAT/	HAA	CEIL-VIS	CAT	DA/	HAT/	HAA	CEIL-VIS
				MDA-VIS	HATH/				MDA-VIS	HATH/		
ASR	22		AB	880/24		462	(500-½)	C	880/40		462	(500-¾)
			D	880/50		462	(500-1)					
	4	AB	880-1		495	(500-1)	C	880-1¼		495	(500-1¼)	
		D	880-1½		495	(500-1½)						
36	AB	880-1		497	(500-1)	C	880-1¼		497	(500-1¼)		
	D	880-1½		497	(500-1½)							
18	AB	880-1		484	(500-1)	C	880-1¼		484	(500-1¼)		
	D	880-1½		484	(500-1½)							
CIRCLING			A	940-1		522	(600-1)	B	960-1		542	(600-1)
			C	960-1½		542	(600-1½)	D	980-2		562	(600-2)

When control tower closed, procedure NA. Visibility reduction by helicopters NA.

EC-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

09295

N1

22 OCT 2009 to 19 NOV 2009

22 OCT 2009 to 19 NOV 2009

RADAR MINS

N2

09295

RADAR INSTRUMENT APPROACH MINIMUMS

FORT WAYNE, IN
FORT WAYNE INTL
 RADAR - 127.2 284.6 ▽ ▲

Amdt 25, JUL 2, 2009 (FAA)

ELEV 814

	RWY	GS/TCH/RPI	CAT	HAT/ HATH/			CAT	HAT/ HATH/			
				DA/ MDA-VIS	HAA	CEIL-VIS		DA/ MDA-VIS	HAA	CEIL-VIS	
ASR	5		AB	1300/24	486	(500-½)	C	1300/40	486	(500-¾)	
			D	1300/50	486	(500-1)	E	1300/60	486	(500-1¼)	
	14		AB	1300-1	498	(500-1)	C	1300-1¼	498	(500-1¼)	
			D	1300-1½	498	(500-1½)	E	1300-1¾	498	(500-1¾)	
	23		AB	1300-1	501	(600-1)	CD	1300-1½	501	(600-1½)	
			E	1300-1¾	501	(600-1¾)					
	32		AB	1260/24	460	(500-½)	C	1260/40	460	(500-¾)	
			DE	1260/50	460	(500-1)					
	CIRCLING			AB	1300-1	486	(500-1)	C	1300-1½	486	(500-1½)
				D	1380-2	566	(600-2)	E	1520-2½	706	(800-2½)

Rwy 5, for inoperative ALSF-2, increase S-5 Cat E visibility ½ mile.
 Rwy 32, for inoperative MALS, increase S-32 Cat E visibility ½ mile.
 LOST COMMUNICATIONS (ALL RWYS): As directed by ATC on initial contact.

GRISSOM ARB (KGUS), IN (Peru) (06159 USAF)
 RADAR - Ctc APP CON - (E) 121.05 318.2 379.3

ELEV 812

	RWY	GS/TCH/RPI	CAT	HAT/ HATH/		
				DA/ MDA-VIS	HAA	CEIL-VIS
ASR ¹	5 ²		AB	1180/24	368	(400-½)
			CDE	1180/40	368	(400-¾)
	23 ³		AB	1260/24	460	(500-½)
			C	1260/40	460	(500-¾)
			DE	1260/50	460	(500-1)
CIR	All Rwy	AB	1340-1	528	(600-1)	
		C	1340-1½	528	(600-1½)	
		D	1380-2	568	(600-2)	
		E	1440-2	628	(700-2)	

¹No-NOTAM preventive maint sked: ASR 1200-1400Z++ Mon. ASR apch svc avbl 1200-0400Z ++dly, (contingent upon manpower and eqpt availability). ²When ALS inop, increase CAT ABC RVR to 50 and vis to 1 mile, CAT DE RVR to 60 and vis to 1¼ miles. ³When ALS inop, increase CAT AB RVR to 50 and vis to 1 mile, CAT C RVR to 60 and vis to 1¼ miles, CAT DE vis to 1½ miles.

22 OCT 2009 to 19 NOV 2009

22 OCT 2009 to 19 NOV 2009

EC-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

09295

N2

RADAR MINS

N3

09295

RADAR INSTRUMENT APPROACH MINIMUMS

MANSFIELD, OH

Amdt. 4A, MAY 7, 2009 (FAA)

ELEV 1297

MANSFIELD LAHM RGNL

RADAR - 124.2 390.8 **▲**

	RWY	GS/TCH/RPI	CAT	HAT/ HATH/			CAT	HAT/ HATH/		
				DA/ MDA-VIS	HAA	CEIL-VIS		DA/ MDA-VIS	HAA	CEIL-VIS
ASR	23		AB	1700-1	405	(500-1)	CD	1700-1¼	405	(500-1¼)
	5		AB	1740-1	443	(500-1)	C	1740-1¼	443	(500-1¼)
CIRCLING			D	1740-1½	443	(500-1½)				
			AB	1760-1	463	(500-1)	C	1760-1½	463	(500-1½)
			D	1880-2	583	(600-2)				

When control tower closed, ASR NA.

TERRE HAUTE, IN

Amdt. 4, MAR 22, 2001 (FAA)

ELEV 589

TERRE HAUTE INTL-HULMAN FIELD

RADAR - 125.45 339.8 **▲**

	RWY	GS/TCH/RPI	CAT	HAT/ HATH/			CAT	HAT/ HATH/		
				DA/ MDA-VIS	HAA	CEIL-VIS		DA/ MDA-VIS	HAA	CEIL-VIS
ASR	5		ABC	920/24	347	(400-½)	DE	920/50	347	(400-1)
	32		ABCD	920-1	331	(400-1)	E	920-1¼	331	(400-1¼)
	23		ABC	940-1	357	(400-1)	DE	940-1¼	357	(400-1¼)
CIRCLING			A	1020-1	431	(500-1)	B	1040-1	451	(500-1)
			C	1040-1½	451	(500-1½)	D	1140-2	551	(600-2)
			E	1240-2¼	651	(700-2¼)				

For inoperative MALSRS, increase S-5 Category D and E visibility to RVR 6000.

Circling not authorized NW of Rws 5/23 for Category E aircraft.

When control tower closed, procedure NA.

TOLEDO, OH

Amdt. 19, AUG 18, 1994 (FAA)

ELEV 684

TOLEDO EXPRESS

RADAR - 134.35 317.55 **▼▲**

	RWY	GS/TCH/RPI	CAT	HAT/ HATH/			CAT	HAT/ HATH/		
				DA/ MDA-VIS	HAA	CEIL-VIS		DA/ MDA-VIS	HAA	CEIL-VIS
ASR	25		ABC	1040-½	362	(400-½)	DE	1040-1	362	(400-1)
	34		ABC	1040-1	372	(400-1)	DE	1040-1¼	372	(400-1¼)
	16		ABC	1060-1	386	(400-1)	DE	1060-1¼	386	(400-1¼)
	7		ABC	1080/24	397	(400-½)	DE	1080/50	397	(400-1)
CIRCLING			AB	1180-1	496	(500-1)	C	1180-1½	496	(500-1½)
			D	1240-2	556	(600-2)	E	1360-2½	676	(700-2½)

Category D S-7 visibility increased to RVR 6000 for inoperative ALSF-2.

Category D S-25 visibility increased to 1¼ miles for inoperative MALSRS.

EC-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

09295

N3

22 OCT 2009 to 19 NOV 2009

22 OCT 2009 to 19 NOV 2009

RADAR INSTRUMENT APPROACH MINIMUMS

YOUNGSTOWN-WARREN, OH

Amdt. 13, OCT 8, 1998 (FAA)

ELEV 1196

YOUNGSTOWN-WARREN RGNL

RADAR - 133.95 322.3 **▽ ▲**

			DA/ HATh/	HAT/ HATH/		DA/ HATh/	HAT/ HATH/			
	RWY	GS/TCH/RPI	CAT	MDA-VIS	HAA	CEIL-VIS	CAT	MDA-VIS	HAA	CEIL-VIS
ASR	5		ABC	1520-1	356	(400-1)	D	1520-1¼	356	(400-1¼)
	14		ABC	1520-½	386	(400-½)	D	1520-1	386	(400-1)
	23		ABC	1580-1	388	(400-1)	D	1580-1¼	388	(400-1¼)
	32		ABC	1580/24	395	(400-½)	D	1580/50	395	(400-1)
CIRCLING			A	1640-1	444	(500-1)	B	1660-1	464	(500-1)
			C	1660-1½	464	(500-1½)	D	1760-2	564	(600-2)

Category D S-14 visibility increased ¼ mile for inoperative MALSRS.

Category D S-32 visibility increased ¼ mile for inoperative MALSRS.

22 OCT 2009 to 19 NOV 2009

22 OCT 2009 to 19 NOV 2009

RADAR INSTRUMENT APPROACH MINIMUMS